COR-599WR NEXT GEN OUTDOOR BULLET w/ ENHANCED DIGITAL WDR



FEATURES

- ANTI VANDAL METAL CONTRUCTION
- CABLE FEED THROUGH BRACKET
- REMOVABLE SUN SHIELD WITH GLARE REDUCING BLACK UNDERCOAT
- 600 TV LINE RESOLUTION

CONTROL OSD THROUGH DVR

SPECIFICATIONS

Video Sensor	1/3" GEN III DSP CCD
Resolution	600 TV Lines
Lens	3.6mm Wide Angle
Min. Illumination	0.5 LUX with infrared ON
Auto White Balance	ATW (OSD Control)
IR Range	80' or more
IR Source	24 infrared LEDs (850nm)
IR Control	Automatic, smart IR Options in OSD Menu
Video Format	Available with NTSC or PAL output
Video signal Output	composit, 1Vp-p @ 75Ohm impedance
Gain Control	AGC (OSD Control)
BLC & HLC	Yes - OSD Control
Weatherproof Rating	1P66 (indoor/outdoor)
Power	DC 12VDC 250mA nominal (~350mA with IR on)
Housing	Heavy duty vandal resistan aluminum alloy
Dimension (inches)	Camera 2.75" diameter
Storage Temperature	-22°F to +140°F (-30°C to +60°C)
Operating Temperature	14°F to +122°F (-14°C to +50°C)
OSD Control	RS485 controled with security DVR menu



ADDITIONAL OSD OPTIONS: MIRROR-FLIP - DZOOM - SCALE - FORMAT - DIGITAL OUT SHADING-PRIVACY MASK -TITLE - GAMMA



COR-599WR