

# VARIFOCAL HDSDI 1080P LONG RANGE OUTDOOR BULLET



SHOWN WITH ECL-210W BRACKET  
SOLD SEPARATELY

## KEY BENEFITS

- ADJUSTABLE SHUTTER SPEED
- EXCELLENT FOR LPR
- ADJUSTABLE IR ILLUMINATION
- 3 MEGA PIXEL RATED LENS
- LONG RANGE IR
- MECHANICAL IR FILTER
- ANALOG VIDEO OUTPUT FOR TEST MONITOR

MODEL : ECL-HD64

## FEATURES

- MEGA PIXEL WITHOUT LIMITS
- OSD ON SCREEN DISPLAY
- ADVANCED WIDE DYNAMIC RANGE
- OPTIMIZED NOISE REDUCTION
- REDUCED CORNER DISTORTION

ADDITIONAL OSD OPTIONS:  
MIRROR-FLIP-DZOOM-SCALE-FPS-FORMAT-DIGITAL OUT  
SHADING-PRIVACY MASK -COMM SET



REAR PANEL



ECL-210W BRACKET-  
SOLD SEPARATELY

## SPECIFICATIONS

| MODEL                  | ECL-HD64-SDI   |
|------------------------|--|
| Video Sensor           | 1/3" CMOS 2 Mega Pixel   |
| Resolution             | 1920 x 1080P   |
| Lens                   | 5-50mm 3 Mega Pixel rated with ICR                                     |
| Illumination Range     | 0.1 LUX (0 LUX IR on)  |
| IR Range               | 120 feet   |
| IR Type                | 52 LED's mixed angle (850nm)   |
| Smart IR               | Yes (OSD Controlled)   |
| Shutter                | Auto/Manual 1/30 ~1/60,000   |
| Flickerless            | Yes (OSD Controlled)   |
| Gain Control           | Auto/Manual  |
| Dynamic Range          | Digital OSD Controlled   |
| Noise Reduction        | Dynamic 2D/3D  |
| Defective Pixel Detect | Yes  |
| BLC & HLC              | Yes  |
| Weatherproof Rating    | IP65 Outdoor   |
| Power / Consumption    | 12VDC/24VAC Dual voltage<br>275mA nominal<br>(700mA with IR on) @12VDC |
| Operating Temperature  | -10~ to 50 °C  |
| Housing                | Aluminum   |
| Dimension(inches)      | 3.5" x 4" x 9.75" (inches)   |
| Weight                 | 3 lb/ 1.4 kg   |
| Operating Temperature  | -10~ to 50 °C  |