

COR-IP5DV

5MP VARIFOCAL NETWORK VANDAL DOME CAMERA



FEATURES

- 1/2.7" Progressive CMOS
- 2.7 ~ 13.5mm (Motorized) IR Lens
- Premium Components
- Wide Dynamic Range
- IR Range up to 115 feet
- Metal Housing IP66 Waterproof
- 2592(H)×1944(V) Resolution



SPECIFICATIONS

Effective Pixels	5MP 2592(H)×1944(V)
Imaging Device	1 / 2.7" Progressive CMOS
Min.Illumination	Color 0.01lux @ F1.2 (AGC ON) ; B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	2.7 ~ 13.5mm (Motorized) H.FOV: 116 ~ 34 °
Shutter	1/5 ~ 1/20000s
Slow Shutter	Support
F No.	F1.8(W) ~ F3.2 (T)±5%
IR Viewable Length	Up to 114.8 feet (35 meters)
Camera Title	On / Off
Day & Night	IR cut filter with auto switch (Day / Night / Auto / Schedule)
Backlight Compensation	Support
ROI	N/A
Video Analytics	N/A
Wide Dynamic Range	Digital WDR
Digital Noise Reduction	3D DNR
Privacy Masking	Support
On-Board Storage	Yes(Micro SD /SDHC /SDXC slot, up to 128 GB)
Alarm Trigger	1 input / 1 output
Audio	1 input (RCA), 1 output (RCA)
Dual Stream	Yes

Interface	RJ45 10M / 100M Ethernet interface x1
Video Compression	H.265 / H.264
Resolution	Mainstream 5MP(2592×1944),4MP(2592x1520) 4MP(2592x1520) 3MP(2304x1296) 1080P(1920x1080) Substream (default 10fps/VGA) 720P(1280x720), VGA(640x480),QVGA(320x240)
Video Bit Rate	8Kbps ~ 8Mbps
Image Settings:	Flip,Rotation ,Saturation, Brightness, Contrast, Hue, Sharpness adjustable
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
System Compatibility	Open Compatibility, (Profile S / G)
Video Output:	Yes
Reset Button	Yes:
POE	Yes
Water Proof	IP 66
Power Supply	DC 12V/POE
Power Consumption	≤ 9W
Storage Temperature	-30~+60°C (-22~+140°F) / less than ≤ 95% RH
Operating Temperature	-30~+55°C (-22~+131°F) / less than ≤ 95% RH
Color / Material	Metal
Dimension (W x H x D)	147 X 117mm (5.78 X 4.6 inches)
Weight	Approximately 2.35 lbs (1067g)

COR-IP5DV

