HYBRID AHD & ANALOG MOTION DETECTOR CAMERA





\circ	\neg	_	\sim 1	_	\sim 1	. —	-		$\overline{}$
-51	~	=		-1	CA	4 1 1		NI.	`

Video Sensor	1/3" 2.4 Megapixel sensor			
Lens	4mm Megapixel rated lens			
Resolution	Digital: 1920×1080P Analog: 960H - 1200TVL			
Video Output	AHD: 1080P / 960P BNC CVBS: 1.0 Vp-p Composite Signal (75 Ω)			
Electronic Shutter	AUTO/ MANUAL /FLK			
Scanning System	Progressive Scan			
Minimum Illumination	0.2 LUX (Color/Day) 0.01 LUX (B/W)			
3D-DNR	OFF / ON (LOW/MIDDLE/HIGH)			
Digital WDR	OFF / ON (Level Adjustable) (Long and short exposure)			
OSD	Yes			
Sens-Up	OFF / ON			
White Balance	AWB/ ATW / PUSH / MANUAL			
Back Light Control	OFF / ON			
D-ZOOM	1.0x - 8.0x			
TV System	NTSC			
Defog	OFF / ON			
Power Consumption	150mA			
Working Temperature	-10°~ to 50°C / -14° +122 °F			
Power	12V DC			
Dimension(D) (H)	4.75 " x 2.75 " (inches) / 120 x 70 (mm)			
Weight	1.32 (lb) / 0.6 (kg)			

Additional OSD Options:

Exposure-wb-manual-special-cam-title-motion-privacy-park-line-image-adjcomm-adj-language-area-state-height-width-mirror-font-contrast-sharpness

KEY BENEFITS

- 2.43 MEGAPIXELSENSOR
- **DUAL OUTPUT: AHD & ANALOG OSD**
- **COVERT INFRARED**
- 4MM FIXED MEGAPIXEL LENS
- PINHOLE LENS FOR COVERT RECORDING

Record covertly with a camera hidden inside a motion detector case. This camera provides the user with crystal clear video images that can be modified from a standard analog signal to an analog high definition signal with a simple touch of the OSD joystick.

- Covert design
- Ball-in-Socket swivel bracket
- Highlight- Backlight compensation
- Advanced OSD menu
- Automatic gain control



