## HIGH RESOLUTION OUTDOOR WEATHERPROOF BULLET



SP		01	TI	$\cap$	10

Video Sensor  I/3" HI-RES Sony Super HAD II Color CCD  Resolution  More than 750 TV Lines  Lens  4.3mm Aspherical Megapixel IR Corrected  Min. Illumination  0.5 LUX ,f1.6 (0.0 LUX with Infrared On)  Auto White Balance  ATW (OSD Control)  IR Range  80' nominal with extended IR range coverage  Dragonfire IR Array  12 infrared LEDs (850nm)  IR Illuminination  DRAGONFIRE automatic IR system, 80ft range  IR Control  Automatic, smart IR Options in OSD Menu  Signal Processing  enhance DSP chipset  Image Control  Sharpness, brightness, color control (OSD)  Synchoronous System  Internal  Shutter  AES (OSD Control)  Dynamic Noise Reduction  Mechanical IR Filter  Mechanical Day / Night ICR-IR cut filter  BLC & HLC  Yes - OSD Control (8 zone)  Day / Night  Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating  Veather Consumption  IR off: 100mA (Max), IR on: 400mA (Max)  Housing  Harden steel case  Dimension (inches)  3"(lenght) x 5.7" (width) x 2.2" (height) (inches)  Weight  1.87 lbs  Storage Temperature  14°F to +113°F (-10°C to +45°C)						
Lens 4.3mm Aspherical Megapixel IR Corrected Min. Illumination 0.5 LUX ,f1.6 (0.0 LUX with Infrared On) Auto White Balance ATW (OSD Control) IR Range 80' nominal with extended IR range coverage Dragonfire IR Array 2 High intensity LEDs (850nm) IR Array 12 infrared LEDs (850nm) IR Illuminination DRAGONFIRE automatic IR system, 80ft range IR Control Automatic, smart IR Options in OSD Menu Signal Processing enhance DSP chipset Image Control Sharpness, brightness, color control (OSD) Synchoronous System Internal Shutter AES (OSD Control) Gain Control AGC (OSD Control) Dynamic Noise Reduction AGC (OSD Control) Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter BLC & HLC Yes - OSD Control (8 zone) Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay Weatherproof Rating 1P66 (indoor/outdoor) Vandal Resistance Hardened case, cable feed-through-bracket Bracket Anti-tamper, cable feed-through bracket included OSD Menu Language English / chinese Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Harden steel case Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height) (inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Video Sensor	1/3" HI-RES Sony Super HAD II Color CCD				
Min. Illumination  Auto White Balance  ATW (OSD Control)  IR Range  Bo' nominal with extended IR range coverage  Dragonfire IR Array  12 High intensity LEDs (850nm)  IR Alray  12 Infrared LEDs (850nm)  IR Illuminination  DRAGONFIRE automatic IR system, 80ft range  IR Control  Automatic, smart IR Options in OSD Menu  Signal Processing  enhance DSP chipset  Image Control  Sharpness, brightness, color control (OSD)  Synchoronous System  Internal  Shutter  AES (OSD Control)  Dynamic Noise Reduction  AGC (OSD Control)  Dynamic Noise Reduction  BLC & HLC  Yes - OSD Control  Privacy  Yes - OSD Control (8 zone)  Day / Night  Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating  Weatherproof Rating  IP66 (indoor/outdoor)  Vandal Resistance  Hardened case, cable feed-through-bracket  Bracket  Anti-tamper, cable feed-through (Max)  Housing  Harden steel case  Dimension (inches)  3"(lenght) x 5.7" (width) x 2.2" (height) (inches)  Weight  1.87 lbs  Storage Temperature  -22°F to +140°F (-30°C to +60°C)	Resolution	More than 750 TV Lines				
Auto White Balance ATW (OSD Control) IR Range 80' nominal with extended IR range coverage Dragonfire IR Array 2 High intensity LEDs (850nm) IR Array 12 infrared LEDs (850nm) IR Illuminination DRAGONFIRE automatic IR system, 80ft range IR Control Automatic, smart IR Options in OSD Menu Signal Processing enhance DSP chipset Image Control Sharpness, brightness, color control (OSD) Synchoronous System Internal Shutter AES (OSD Control) Gain Control AGC (OSD Control) Dynamic Noise Reduction AGC (OSD Control) Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter BLC & HLC Yes - OSD Control Privacy Yes - OSD Control (8 zone) Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay Weatherproof Rating 1P66 (indoor/outdoor) Vandal Resistance Hardened case, cable feed-through-bracket Bracket Anti-tamper, cable feed-throught bracket included OSD Menu Language English / chinese Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Harden steel case Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height) (inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Lens	4.3mm Aspherical Megapixel IR Corrected				
IR Range 80' nominal with extended IR range coverage Dragonfire IR Array 2 High intensity LEDs (850nm) IR Array 12 infrared LEDs (850nm) IR Iluminination DRAGONFIRE automatic IR system, 80ft range IR Control Automatic, smart IR Options in OSD Menu Signal Processing enhance DSP chipset Image Control Sharpness, brightness, color control (OSD) Synchoronous System Internal Shutter AES (OSD Control) Gain Control AGC (OSD Control) Dynamic Noise Reduction 2 DNR (OSD Control) Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter BLC & HLC Yes - OSD Control (8 zone) Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay Weatherproof Rating 1P66 (indoor/outdoor) Vandal Resistance Hardened case, cable feed-through-bracket Bracket Anti-tamper, cable feed-throught bracket included OSD Menu Language English / chinese Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Harden steel case Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height) (inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Min. Illumination	0.5 LUX ,f1.6 (0.0 LUX with Infrared On)				
Dragonfire IR Array  IR Array  12 Infrared LEDs (850nm)  IR Iluminination  DRAGONFIRE automatic IR system, 80ft range  IR Control  Automatic, smart IR Options in OSD Menu  Signal Processing  enhance DSP chipset  Image Control  Sharpness, brightness, color control (OSD)  Synchoronous System  Internal  Shutter  AES (OSD Control)  Qain Control  AGC (OSD Control)  Dynamic Noise Reduction  Mechanical IR Filter  BLC & HLC  Privacy  Yes - OSD Control (8 zone)  Day / Night  Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating  Weatherproof Rating  Vandal Resistance  Hardened case, cable feed-throught bracket included  OSD Menu Language  English / chinese  Power  DC 12VDC (sold separately)  Power / Consumption  IR off: 100mA (Max), IR on: 400mA (Max)  Housing  Harden Hardenes  -22°F to +140°F (-30°C to +60°C)	Auto White Balance	ATW (OSD Control)				
IR Array  12 infrared LEDs (850nm)  IR Iluminination  DRAGONFIRE automatic IR system, 80ft range  IR Control  Automatic, smart IR Options in OSD Menu  Signal Processing  enhance DSP chipset  Image Control  Sharpness, brightness, color control (OSD)  Synchoronous System  Internal  Shutter  AES (OSD Control)  Gain Control  AGC (OSD Control)  Dynamic Noise Reduction  Mechanical IR Filter  BLC & HLC  Yes - OSD Control  Privacy  Yes - OSD Control (8 zone)  Day / Night  Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating  1P66 (indoor/outdoor)  Vandal Resistance  Hardened case, cable feed-through-bracket  Bracket  Anti-tamper, cable feed-through bracket included  OSD Menu Language  Power  DC 12VDC (sold separately)  Power / Consumption  IR off: 100mA (Max), IR on: 400mA (Max)  Housing  Harden steel case  Dimension (inches)  3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight  1.87 lbs  Storage Temperature  -22°F to +140°F (-30°C to +60°C)	IR Range	80' nominal with extended IR range coverage				
IR Iluminination DRAGONFIRE automatic IR system, 80ft range IR Control Automatic, smart IR Options in OSD Menu Signal Processing enhance DSP chipset Image Control Sharpness, brightness, color control (OSD) Synchoronous System Internal Shutter AES (OSD Control) Gain Control AGC (OSD Control)  Dynamic Noise Reduction 2 DNR (OSD Control) Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter BLC & HLC Yes - OSD Control Privacy Yes - OSD Control (8 zone)  Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay Weatherproof Rating 1P66 (indoor/outdoor) Vandal Resistance Hardened case,cable feed-through-bracket Bracket Anti-tamper, cable feed-throught bracket included OSD Menu Language English / chinese Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Harden steel case Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Dragonfire IR Array	2 High intensity LEDs (850nm)				
IR Control Automatic, smart IR Options in OSD Menu  Signal Processing enhance DSP chipset  Image Control Sharpness, brightness, color control (OSD)  Synchoronous System Internal  Shutter AES (OSD Control)  Gain Control AGC (OSD Control)  Dynamic Noise Reduction 2 DNR (OSD Control)  Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter  BLC & HLC Yes - OSD Control  Privacy Yes - OSD Control (8 zone)  Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating 1P66 (indoor/outdoor)  Vandal Resistance Hardened case, cable feed-through-bracket  Bracket Anti-tamper, cable feed-throught bracket included  OSD Menu Language English / chinese  Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	IR Array	12 infrared LEDs (850nm)				
Signal Processing enhance DSP chipset  Image Control Sharpness, brightness, color control (OSD)  Synchoronous System Internal  Shutter AES (OSD Control)  Gain Control AGC (OSD Control)  Dynamic Noise Reduction 2 DNR (OSD Control)  Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter  BLC & HLC Yes - OSD Control  Privacy Yes - OSD Control (8 zone)  Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating 1P66 (indoor/outdoor)  Vandal Resistance Hardened case,cable feed-through-bracket  Bracket Anti-tamper, cable feed-throught bracket included  OSD Menu Language English / chinese  Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	IR Iluminination	DRAGONFIRE automatic IR system, 80ft range				
Image Control Sharpness, brightness, color control (OSD) Synchoronous System Internal Shutter AES (OSD Control) Gain Control AGC (OSD Control) Dynamic Noise Reduction 2 DNR (OSD Control) Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter BLC & HLC Yes - OSD Control Privacy Yes - OSD Control (8 zone) Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay Weatherproof Rating Vandal Resistance Hardened case, cable feed-through-bracket Bracket Anti-tamper, cable feed-throught bracket included OSD Menu Language English / chinese Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Harden steel case Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	IR Control	Automatic, smart IR Options in OSD Menu				
Synchoronous System Shutter AES (OSD Control) Gain Control AGC (OSD Control) Dynamic Noise Reduction Mechanical IR Filter BLC & HLC Privacy Yes - OSD Control (8 zone) Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay Weatherproof Rating 1P66 (indoor/outdoor) Vandal Resistance Hardened case,cable feed-through-bracket Bracket Anti-tamper, cable feed-throught bracket included OSD Menu Language Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Signal Processing	enhance DSP chipset				
Shutter AES (OSD Control)  Gain Control AGC (OSD Control)  Dynamic Noise Reduction 2 DNR (OSD Control)  Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter  BLC & HLC Yes - OSD Control  Privacy Yes - OSD Control (8 zone)  Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating 1P66 (indoor/outdoor)  Vandal Resistance Hardened case,cable feed-through-bracket  Bracket Anti-tamper, cable feed-throught bracket included  OSD Menu Language English / chinese  Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	Image Control	Sharpness, brightness, color control (OSD)				
Gain Control  Dynamic Noise Reduction  AGC (OSD Control)  Dynamic Noise Reduction  Mechanical IR Filter  BLC & HLC  Privacy  Privacy  Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating  Tefé (indoor/outdoor)  Vandal Resistance  Hardened case, cable feed-through-bracket  Bracket  Anti-tamper, cable feed-throught bracket included  OSD Menu Language  Power  DC 12VDC (sold separately)  Power / Consumption  IR off: 100mA (Max), IR on: 400mA (Max)  Housing  Harden steel case  Dimension (inches)  3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight  1.87 lbs  Storage Temperature  2 DNR (OSD Control)  AGC (OSD Control)  Adjustable Day - Night ICR - IR cut filter  BLC & AGC (OSD Control)  Adjustable Day - Night ICR - IR cut filter  BLC & AGC (OSD Control)  Adjustable Day - Night ICR - IR cut filter  BLC & AGC (OSD Control)  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable Day - Night ICR - IR cut filter  Adjustable	Synchoronous System	Internal				
Dynamic Noise Reduction 2 DNR (OSD Control)  Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter  BLC & HLC Yes - OSD Control  Privacy Yes - OSD Control (8 zone)  Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating 1P66 (indoor/outdoor)  Vandal Resistance Hardened case,cable feed-through-bracket  Bracket Anti-tamper, cable feed-throught bracket included  OSD Menu Language English / chinese  Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	Shutter	AES (OSD Control)				
Mechanical IR Filter Mechanical Day / Night ICR-IR cut filter  BLC & HLC Yes - OSD Control  Privacy Yes - OSD Control (8 zone)  Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating 1P66 (indoor/outdoor)  Vandal Resistance Hardened case,cable feed-through-bracket  Bracket Anti-tamper, cable feed-throught bracket included  OSD Menu Language English / chinese  Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	Gain Control	AGC (OSD Control)				
BLC & HLC Privacy Yes - OSD Control Privacy Yes - OSD Control (8 zone)  Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay Weatherproof Rating Vandal Resistance Hardened case,cable feed-through-bracket Bracket Anti-tamper, cable feed-throught bracket included OSD Menu Language English / chinese Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Harden steel case Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Dynamic Noise Reduction	2 DNR (OSD Control)				
Privacy Yes - OSD Control (8 zone)  Day / Night Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating 1P66 (indoor/outdoor)  Vandal Resistance Hardened case,cable feed-through-bracket  Bracket Anti-tamper, cable feed-throught bracket included  OSD Menu Language English / chinese  Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	Mechanical IR Filter	Mechanical Day / Night ICR-IR cut filter				
Day / Night  Adjustable Day-to-Night and Night-to-Day threshold and delay  Weatherproof Rating  1P66 (indoor/outdoor)  Vandal Resistance  Hardened case,cable feed-through-bracket  Bracket  Anti-tamper, cable feed-throught bracket included  OSD Menu Language  English / chinese  Power  DC 12VDC (sold separately)  Power / Consumption  IR off: 100mA (Max), IR on: 400mA (Max)  Housing  Harden steel case  Dimension (inches)  3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight  1.87 lbs  Storage Temperature  -22°F to +140°F (-30°C to +60°C)	BLC & HLC	Yes - OSD Control				
delay  Weatherproof Rating 1P66 (indoor/outdoor)  Vandal Resistance Hardened case,cable feed-through-bracket  Bracket Anti-tamper, cable feed-throught bracket included  OSD Menu Language English / chinese  Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	Privacy	Yes - OSD Control (8 zone)				
Vandal Resistance Hardened case, cable feed-through-bracket Bracket Anti-tamper, cable feed-throught bracket included OSD Menu Language English / chinese Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Harden steel case Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Day / Night					
Bracket Anti-tamper, cable feed-throught bracket included OSD Menu Language English / chinese Power DC 12VDC (sold separately) Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max) Housing Harden steel case Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches) Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Weatherproof Rating	1P66 (indoor/outdoor)				
OSD Menu Language English / chinese  Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	Vandal Resistance	Hardened case,cable feed-through-bracket				
Power DC 12VDC (sold separately)  Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	Bracket	Anti-tamper, cable feed-throught bracket included				
Power / Consumption IR off: 100mA (Max), IR on: 400mA (Max)  Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	OSD Menu Language	English / chinese				
Housing Harden steel case  Dimension (inches) 3"(lenght) x 5.7" (width) x 2.2" (height)(inches)  Weight 1.87 lbs  Storage Temperature -22°F to +140°F (-30°C to +60°C)	Power	DC 12VDC (sold separately)				
Dimension (inches)         3"(lenght) x 5.7" (width) x 2.2" (height)(inches)           Weight         1.87 lbs           Storage Temperature         -22°F to +140°F (-30°C to +60°C)	Power / Consumption	IR off: 100mA (Max), IR on: 400mA (Max)				
Weight 1.87 lbs Storage Temperature -22°F to +140°F (-30°C to +60°C)	Housing	Harden steel case				
Storage Temperature -22°F to +140°F (-30°C to +60°C)	Dimension (inches)	3"(lenght) x 5.7" (width) x 2.2" (height)(inches)				
	Weight	1.87 lbs				
Operating Temperature 14°F to +113°F (-10°C to +45°C)	Storage Temperature	-22°F to +140°F (-30°C to +60°C)				
	Operating Temperature	14°F to +113°F (-10°C to +45°C)				

## **FEATURES**

- 2.1 INTERLACE SCANNING SYSTEM
- 1/3" SONY SUPER HAD II
- DRAGONFIRE IR ARRAY
- 750 TV LINE RESOLUTION
- INTERGRATED GLASS LENS SEPARATOR

## OSD CONTROL FEATURES

- MOTION DETECTION
- **BLEMISH COMPENSATION**
- MIRROW (H-REV) SHARPNESS DNR
- SHARPNESS -AUTO WHITE BALANCE



ADDITIONAL OSD OPTIONS: MIRROR-FLIP - DZOOM - SCALE - FORMAT - DIGITAL OUT SHADING-PRIVACY MASK -TITLE - GAMMA