## MINI INTERIOR/EXTERIOR COMPARTMENT CAMERA





POSITION EXAMPLES

SPECIFICATIONS	
Video Sensor	1/4" color CCD
Lens	3.6mm with 160-degree field of view
Resolution	700-TV lines
Minimum Illumination	0.05 LUX
Shutter	Auto-electronic shutter (AES) (1/10th to 1/100,000 sec.)
AWB	Auto-White Balance
AGC	Auto-Gain Control
Signal to Noise	>50dB
Bracket	Adhesive backed acrylic housing
Video Format	NTSC or PAL
Video Signal	Composite color video, 1Vp-p 75-ohm
Cables	Breakout cable and extension cable with RCA plugs included
Dimensions	1" LONG x 7/8" WIDE x 1/2" TAII
Weatherproof	Yes, IP68 Can be mounted on exterior of vehicle or used in outdoor covert applications.
Power	9VDC to 16VDC (120mA nominal)
Power Requirement	Uses vehicle 12VDC power

## **FEATURES**

- **INCREASE SAFETY** RECORD PASSENGER CONDUCT MONITOR CARGO SHIFT
- HIGH RESOLUTION **FULL COLOR IMAGING**
- RUGGED DESIGN
- ORBITAL BRACKET
- CONTINUOUS OPERATION OVER THE ROUGHEST ROADS
- LESS NOISE, BETTER LOW LIGHT SENSITIVITY
- SMALLEST CCD EVER



Superimpose parking guides lines appear on-screen to aid parking the vhicle. Useful when the camera is mounted on the back of the vehicle. If not desired, cut this

Smaller than a quarter this Mini Size Camera is easy to place anywhere in a vehicle or covert design.



25' EXTENSION CABEL