

COR-HDS25

HD-SDI FULL 1080p OUTDOOR PTZ w/ MEGAWATT IR SYSTEM



KEY FEATURES

- 1/2.7" PROGRESSIVE SCAN CMOS
- 1080P HD-SDI @ 30 FRAMES PER SECOND
- 20X OPTICAL ZOOM WITH AUTO FOCUS
- 400° PER SECOND MAX SPEED
- 5 LEVELS OF DIGITAL NOISE REDUCTION
- MECHANICAL IR CUT FILTER
- SLOW SHUTTER SENSE-UP
- SPHERICAL PRIVACY ZONE MASKING (24 ZONES W VARIOUS PTZ CONTROLS)
- 3 LEVELS OF LIGHTNING AND SURGE PROTECTION
- 2 MEGAPIXEL IMAGE SENSOR
- INTELLIGENT IR ILLUMINATION - IR SYSTEM MOVES IN SYNC WITH CAMERA
- SMART PATTERN RECORDING
- COMPLETE SONY SOLUTION (FCB-EH6300)
- 20X OPTICAL ZOOM
12X DIGITAL (240 TOTAL)

SPECIFICATIONS

CAMERA	
Resolution	1080P FULL HD-SDI
Sensor	1/2.8"-type Exmor™ CMOS
Image Sensor	2 megapixel
Effective Pixels	Approximately 2 million
Progressive Scanning	Yes
Lens	Optical Magnification : 20X, Focal Distance: 4.7 - 94.0mm
Minimum Illumination	0.5 Lux
Focus	Auto, Manual
Infrared Cut	Auto, Manual
Automatic Gain Control	Auto, Manual
Iris	Auto, Manual
Back Light Compensation	Auto, Manual
White Balance	Auto, Manual
Video Output	(Y: 8bit, C: 8bit, HSYNC, VSYNC, DCLK)
Video Format	720P/30 - 1080P/30
Camera Module Control Interface	Sony VISCA(Signal level 3.3V), baud rate: 96 Kb/s, 19.2 Kb/s, 38.4 Kb/s stop bit selectable
DOME	
Horizontal Viewing Angle	54.1° (wide end) - 2.9° (tele end)
Housing	Metal body construction-ABS lower unit
Weatherproof rating	IP66
Pan range	360° Infinite Continuous Rotation
Tilt range	0°~93° Auto Flip 180°
Manual Tilt speed	0.02~160°/S



20X
OPTICAL
ZOOM



Function Parameters	
Operation Menu	Multiple Languages for OSD menu, English, Spanish etc
Pan and Tilt	360° continuous pan rotation, 90° tilt range
Image sensor	2 megapixel 1080P
IR Parameters	
Pulse Width Modulation	Yes
Support ambient light detection	IR illumination on 1-15 grades selectable
Infrared LEDs	IR Megawatt high power system
Infrared Distance	150m (450 feet)
Flashlight	No White light , Infrared model
Weight and Dimensions	
Weight	5~7kg 11 lbs
Certificates	IP66, ROHS, CE, FCC

COR-HDS25

