## NUBIX16XQ ENTERPRISE 16 CHANNEL DVR w/ REAL TIME RECORDING & PLAYBACK

## Compatible with ORBIX/NUBIX HD





|                                     | SPECIFICATIONS  |
|-------------------------------------|---|
| * GENERAL                           |   |
| Performance                         | Pentaplex   |
| Display speed                       | Real time   |
| Record speed                        | NTSC: 240fps @ 960H / PAL: 200fps @ 960H  |
| Video In /Analog Camera<br>Loop Out | 16 / 16(BNC)  |
| Video Out /display                  | 1 HDMI, 1 VGA   |
| Video Out /resolution               | 1920x1080, 1600x1200, 1440x900, 1280x1024, 1280x720, 1024x968                           |
| Video Out /Spot (CVBS)              | 1 BNC   |
| Audio/ Input / Output               | 8/1   |
| Sensor Alarm Input /<br>Output      | 8/2   |
| * DETAILS                           |   |
| Screen/ Display split               | 1, 4, 7, 9, 10, 13, 16  |
| Screen /interface                   | Graphic User Interface  |
| Video/Codec                         | H.264   |
| Video/Image quality                 | Highest / High / Normal / Low   |
| Video/Recording type                | Schedule / Normal / Event (Motion, Sensor, Videoloss)                                   |
| Storage/Internal                    | 2 HDDs x 4TB (1 HDD + DVD-RW)   |
| Storage/Option                      | Add SATA Board: 3 HDDs or 2 HDDs + DVD-RW   |
| Connectors/ USB / RS-485            | 2 USB ports / PTZ camera, PTZ controller interface                                      |
| * FUNCTIONS                         |   |
| Camera option                       | Color adjustment/Position change / Freeze / 4X digital zoom (live/ playback)            |
| Motion/Sensitivity                  | 5 levels motion detection   |
| Motion/Area                         | Adjustable GRID (22 x 15)   |
| System/Hidden Camera                | Hidden camera on live monitoring  |
| System/PTZ                          | Various PTZ camera protocol / Preset up to 255 / RS-485                                 |
| System/Private Zone                 | Blocking the private zone (live / playback)   |
| System/Auto Time Sync               | NTP (Network Time Protocol)   |
| System/Firmware Update              | USB   |
| System/S.M.A.R.T.                   | Auto detect when HDD's problem  |
| Event/Type                          | Motion / Sensor / Video loss  |
| Event/Action                        | Recording, E-Mail, Log, Send message to remote, Buzzer, Pop<br>up,<br>Alarm, PTZ preset |
| Event/Pre/Post Recording            | Up to 60sec / 100sec  |
| Backup/ File format                 | DVR format  |
| Backup/ Media                       | DVD / USB device / Network  |
| Network/Type                        | Static IP / DHCP / DDNS   |
| Network/Base-T                      | 10/100/1000 Mbps  |
| Network/Browser                     | CMS, Web viewer (Windows/MAC OS), Smart phone support<br>(iPhone, iPad, Android)        |

## **KEY FEATURES**

- 16 CHANNEL 960H H.264 DVR
- CMS PROGRAM
- REAL HD RESOLUTION SUPPORT (HDMI PORT)
- 2 HDDs x 4TB (1 HDD + DVD-RW or eSATA)
- 1 SPOT MONITOR OUTPUT
- VERSATILE PLAYBACK FUNCTIONS
- GIGABIT LAN
- WINDOWS AND MAC PC COMPATIBLE WEB VIEWER
- SMARTPHONE VIEWER (IPHONE, IPAD, ANDROID)
- 480 FPS REAL TIME 960H (960 X 480) RECORDING & PLAYBACK
- DUAL MODE OPERATION / SMART SEARCH / SECTION REPEAT PLAYBACK

FRONT VIEW



| * SEARCH /PLAYBACK      |  |
|-------------------------|--|
| Speed                   | 5 steps  |
| Quick / Event search    | Real time  |
| Record speed            | Search by designated time / Search by event                      |
| Section repeat playback | Playback repeating designated time section only                  |
| Panorama search         | Searching each frame in a screen simultaneously                  |
| SMART search            | SMART search   |
| Dual mode function      | Live monitoring during playback                                  |
| * POWER                 |  |
| Operating Temperature   | 0~45°C, 32~113°F   |
| Humidity                | 5~85%  |
| Power requirement       | DC 12V 5A  |
| * PHYSICAL (WITHOUT H   | DD)  |
| Dimensions (W x H x D)  | 440(W) x 430(D) x 90(H) (mm) 17.3(W) x 16.9(D) x 3.5(H) (inches) |
| Weight                  | 7 (kg ) 15.4 (pounds)  |

**NUBIX16XQ** 

©2016 Cortex® As our product is subject to continuous improvement, Cortex & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE\_ Distributed by www.cortexcctv.com 01-06132016