

# COR-IP5FISHC

## 5MP PANORAMIC FISH EYE NETWORK CAMERA with INFARED



### KEY FEATURES

- 1/2.9" Progressive CMOS
- 1.1mm IR Lens, 360° Angle of View
- Premium Components
- Dwarping Technology
- IR Range 15 feet radius 30 feet dia.
- IP56 indoor use
- 2160 (H) × 2160 (V) Resolution

### SPECIFICATIONS



Resolution	5MP 2160(H)×2160(V)
Image Sensor	1/2.9" Progressive CMOS (6.82M pixels)
Min.Illumination	Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter Time	Auto/Manual 1/5 ~ 1/20000s
Lens	1.1mm , Angle of view: 360°
F No.	F 2.0 ±5%
Day & Night	Auto switching infrared-cut filter (OSD on/off)
WDR	Digital
Video compression	H.265 / H.264
Video Bit Rate	8Kbps ~ 8Mbps
Video Streaming	3 individually adjustable streams
Frame Rate	Mainstream 5MP (2160×2160) 1520x1520,1080x1080 , 720x720 Substream 720x720,480x480,240x240 Mobilestream 480x480, 240x240
Image Settings	Image rotate, Saturation, Contrast, Hue, Brightness, Sharpness
BLC	Supported
ROI	Supported
Privacy Mask	Supported

Protocols	TCP/IP,IPv4v6,HTTP,DHCP,DNS, DDNS,RTP/RTSP,PPPoE, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Compatibility	Open Compatibility, API, CortexPlug&Play
Network Interface	RJ45 10M / 100M Ethernet interface
Illumination	3pcs (SMD)
IR range	15 feet (5m ) 30 feet dia.
SD Card	Internal
Alarm Trigger	Yes, Screw Terminal
Audio	Yes
Video Output	Yes
Reset System	Hardware reset button and software
PoE	Yes
Casing	IP56 (indoor)
Power Supply	DC 12V / POE
Consumption	≤ 5W
Storage Temperature	-30~+60°C (-22~+140°F)
Operating Temperature	-30~+55°C (-22~+131°F)
Dimensions	120 X 55mm (4.72 X 2.16 inches)
Weight	Approximately .88 lbs (400g )

COR-IP5FISHC

