

COR-IP5PE

5MP WIDE ANGLE NETWORK CAMERA



FEATURES

- 1/2.7" Progressive CMOS
- 2.8 mm IR Lens approx. 92° H.FOV
- Premium Components
- 12 LEDS
- IR Range up to 32 feet
- Metal Housing IP66 Waterproof
- 2592 (H) ×1944 (V) Resolution



SPECIFICATIONS

Resolution	5MP 2592(H)×1944(V)
Image Sensor	1/2.7" Progressive CMOS
Min.Illumination	Color 0.05lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter Time	1/5 ~ 1/20000s
Slow Shutter	Support
Lens	2.8 mm H.FOV: 92°
Day & Night	IR cut filter with auto switch (Day/Night/Auto/Schedule)
WDR	Digital WDR
Digital noise reduction	3D DNR
Video compression	H.265 / H.264
Video Bit Rate	256Kbps ~ 8Mbps
Video Streaming	Dual
Frame Rate	Mainstream Up to 15fps 5MP(2592×1944),4MP(2592x1520) 3MP(2048x1520),1080P(1920x1080), 960P(1280x960), 720P(1280x720) Substream VGA(640x480), QVGA(320x240)
Image Settings	Flip mode, Saturation, Brightness, Con- trast, Hue, Sharpness adjustable
BLC	Supported
Privacy Mask	Supported

AI Analytics	N/A
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS, RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNM P,HTTPS,FTP
Compatibility	Open Compatibility (Ver 2.6)
Network Interface	RJ45 10M / 100M Ethernet interface x1
LED	12pcs
IR Range	Up to 32 feet (10m)
SD Storage	Yes (internal)
Alarm Trigger	No
Microphone	Yes
Video output	No
Reset Button	No
SD Card	Internal
PoE	Yes IEEE 802.3af / IEEE 802.3at
Casing	Metal Housing IP66 Waterproof
Power Supply	DC 12V / PoE
Consumption	≤ 7W
Storage Temperature	-30~+60°C (-22~+140°F)
Operating Temperature	-30~+55°C (-22~+131°F)
Dimensions	119 X 64 mm (4.6 X 2.5 inches)
Weight	Approximately .99 lbs (450g)

COR-IP5PE

