

COR-IP5TRVAG

5MP VARIFOCAL NETWORK CAMERA with MOTORIZED ZOOM



KEY FEATURES

- 1 / 2.7" Progressive CMOS
- 2.7 ~ 13.5mm (Motorized) IR Lens
- Premium Components
- Slow Shutter Support
- IR Range up to 147 feet

| | |
|-----------------------------------|--|
| Hardware Reset | Yes |
| Ethernet | RJ45 (10 / 100BASE-T) |
| Video Compression Format | H.265 / H.264 |
| Resolution | Mainstream 5MP(2592×1944),4MP(2592×1520) 3MP(2304×1296),1080P(1920×1080) 960P(1280×960),720P(1280×720) Substream 720P(1280×720),VGA(640×480),QVGA(320×240) Mobilestream VGA(640×480), QVGA(320×240) |
| Max. Framerate | 50Hz: 25fps@5MP/4MP/3MP/2MP/960P/720P/ VGA/QVGA 60Hz: 30fps@5MP/4MP/3MP/2MP/960P/720P/ VGA/QVGA |
| Video Quality Ajustment | 8Kbps ~ 8Mbps |
| Bitrate control method | CBR/VBR |
| Streaming Capability | Triple-Stream (Main / Sub / Mobile) |
| IP | IPv4 |
| Image Settings | Image rotate, Saturation, Contrast, Hue, Brightness, Sharpness |
| Protocol | TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,SMTP,NTP,UPnP,SNMP,HTTPS,FTP, |
| Security | IP address filter;complicated password;Authenticated username and password |
| Streaming Method | Unicast / Multicast |
| Max. User Access | Max 7 (admin+user) |
| Application Programming Interface | Open Compatibility,(Profile S / G / T) |
| Web Viewer | IE8,9,10,11, Chrome 44/lower, Firefox 51/lower, Safari 11/lower |
| Illumination | DragonFire® 1pc (Cortex Matrix Array) LED |
| Ingress Protection | Metal Housing IP66 Waterproof |
| Input Voltage / Current | D12V /POE (IEEE802.3af) |
| Power Consumption | 4.8W |
| Storage Conditions | -30~+60°C (-22~+140°F) / less than ≤ 95% RH |
| Operating Conditions | -30~+55°C (-22~+131°F) / less than ≤ 95% RH |
| Color / Material | Gray / Metal |
| Dimension (W x H x D) | 135 x 135 x 127mm (5.3 x 5 x 5 inches) |
| Weight | Approximately 474g (1.04 lbs) |

SPECIFICATIONS

| | |
|---------------------------|---|
| Effective Pixels | 5MP 2592(H)×1944(V) |
| Imaging Device | 1 / 2.7" |
| Scanning System | Progressive CMOS |
| Min.Illumination | Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON |
| Focal Length (Zoom Ratio) | 2.7 - 13.5 mm |
| Max. Aperture Ratio | F No. 1.83 (W) ~ 3.32(T) |
| Lens Type | Motorized(Ø14) |
| Angular Field of View | Horizontal: 101 ~ 31°, Vertical: 71 ~ 23°, Diagonal: 138 ~ 38° |
| Min. Object Distance | 0.2M~INF |
| IR Viewable Length | Up to 147 feet (45m) |
| Camera Title | On / Off |
| Day & Night | IR cut filter with auto switch (Day / Night / Auto / Schedule) |
| Backlight Compensation | Off / On (5 Zone) |
| Wide Dynamic Range | WDR |
| Digital Noise Reduction | 3D DNR |
| Motion Detection | Off / On (8 Level) |
| Privacy Masking | Off / On (4 Zone, Rectangle) |
| Gain Control | Auto |
| White Balance | Auto / Manual / Indoor |
| Electronic Shutter Speed | 1/5 ~ 1/20000s |
| Flip / Mirror | Flip / Rotation |
| On-Board Storage | Micro SD slot, up to 256GB |
| Alarm | 1 input, 1 output |
| Audio | 1 input (RCA), 1 output (RCA) |
| Smart Feature | PID,LCD,PD/VD, FD |

COR-IP5TRVAG

